

# No. 98557-8-9N

## Bold Cables Coat

Although we make every effort to prevent errors from being published, we regret that they do occur and apologize for any inconvenience this may cause. The Cables have been changed on the Front of this pattern, and one row of the Left Front pattern. Please note the **new** instructions below. Also note, there may be more than one revision to a pattern.

**C6B** Slip next 3 sts onto cable needle and hold to back of work, k3 from left-hand needle, then k3 from cable needle.

### Right Front:

**Note:** When working the Cable Pattern, work C6F only each time Row 3 of pattern is worked.

### Left Front:

**Note:** When working the Cable Pattern, work C6B only each time Row 3 of pattern is worked.

### Under To Shape Armhole and Front Neck:

Keeping patterns correct, continue as follows:

**Next Row:** Cast off 2(2, 2, 3) sts, work in pattern to end - 17(19, 21, 22) sts. Place a marker at end of last row to indicate beg of neck shaping.

**Next Row:** Work in pattern to end.

**Next Row:** (right side) **K1, work 2tog, work in pattern to last 12 sts, work 2tog, work in pattern to end.** Now continue to dec one st at armhole edge on every right side row 1(3, 3, 3) times AND AT THE SAME TIME, dec one st at neck edge before 1st marker (as before), one every 4th row following 3(3, 3, 4) times more.

When Finishing, sew together Left and Right Collars at center back.

As of February 2015 the printed pattern has been revised. We apologize for any inconvenience.